

NOKTOP HAKKA TRAILER

Trailer retread for every road, in every weather

PRODUCT CODES T672912, T672913, T672914,
T672915, T672916, T672917,
T672927, T672928

APPLICATION Trailer

USAGE Long haul, Regional



TECHNICAL DATA

Product code	Name	Width	Length	Pattern depth	Weight per meter	Weight
T672912	Nokian Tyres Noktop Hakka Trailer 300	300 mm	3350 mm	14 mm	5.5 kg/m	18.3 kg/pcs
T672913	Nokian Tyres Noktop Hakka Trailer 325	325 mm	3350 mm	14 mm	5.9 kg/m	19.7 kg/pcs
T672914	Nokian Tyres Noktop Hakka Trailer 220	220 mm	3350 mm	13.5 mm	3.5 kg/m	11.7 kg/pcs
T672915	Nokian Tyres Noktop Hakka Trailer 230	230 mm	3350 mm	13.5 mm	3.7 kg/m	12.3 kg/pcs
T672916	Nokian Tyres Noktop Hakka Trailer 240	240 mm	3350 mm	13.5 mm	3.9 kg/m	13.1 kg/pcs
T672917	Nokian Tyres Noktop Hakka Trailer 255	255 mm	3350 mm	13.5 mm	4.1 kg/m	13.9 kg/pcs
T672927	Nokian Tyres Noktop Hakka Trailer 220 Short	220 mm	3070 mm	13.5 mm	3.5 kg/m	10.7 kg/pcs
T672928	Nokian Tyres Noktop Hakka Trailer 230 Short	230 mm	3070 mm	13.5 mm	3.6 kg/m	11 kg/pcs

WINTER MARKINGS M+S, SnowGrip

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS